



	Classic	Hi-power®	Power Plus	Super HC®	CRE Plus	Quad-Power® III	Predator®	Powerated®	Polyflex®	Micro-V®
Vermogen		12*B46		8*SPB1250		5*XPB1250	4*SPBP2000		6*11M2300	PM2286/14
115 KW 1500omw/min										
2* 300 mm schijf										
Schijfbreedte mm		234		158		101	82		95	135
Levensduur (uren)		25.000		25.000		25.000	25.000		25.000	
Profiel-afmetingen b*h	Z 10*6	Z 10*6	SPZ 10*6	SPZ 10*6	XPZ 10*8 /3VX 10*8	XPZ 10*8 /3VX 10*8		3L 3/8*7/32	3M 3*2,28	PJ 2,34*3,6
Vermogen licht			9J / 3V 10*8	9J / 3V 10*8			9JP 10*8		5M 5*3,3	PL 4,7*6,4
Vermogen middel	A 13*8	A 13*8	SPA 13*10	SPA 13*10	XPA 13*10	XPA 13*10	AP 13*8	4L 1/2*5/16	7M 7*533	PM 9,4*12,5
	B 17*11	B 17*11	SPB 16*13	SPB 16*13	XPB 16*13/5VX16*13	XPB 16*13/5VX16*13	BP /SPBP 16*13	5L 21/32*3/8	11M 11*6,85	
			15J/5V 16*13	15J/5V 16*13			15JP 16*23			
Vermogen zwaar	C 22*14	C 22*14	SPC 22*18	SPC 22*18	XPC 22*18	XPC 22*18	CP /SPCP 22*18			
		D 32*19	8V/25J 26*23	8V/25J 26*23			8VP 26*23			
V-groef ISO 4183 DIN 2211	36°-38°	36°-38°	36°-38°	36°-38°	36°-38°	36°-38°	36°-38°		60°-62°	40°
DIN 2217 ISO 5290										
Min. Diameter mm	Z= 60	Z= 60	SPZ= 71	SPZ= 71	XPZ= 56	XPZ= 56				PJ=20
			9J = 71	9J = 71			9JP = 71			PL=75
	A= 85	A= 85	SPA= 100	SPA= 100	XPA= 80	XPA= 80	AP = 80			PM=180
	B= 112	B= 112	SPB=160	SPB=160	XPB= 112	XPB= 112	BP =140 SPBP=160			
			15J= 160	15J= 160			15JP=180			
	C=180	C=180	SPC=250	SPC=250	XPC= 180	XPC= 180	CP=236 /SPCP=250			
	D=315	D=315	8V/25J=315	8V/25J=315			8VP= 432			
Statisch geleidend ISO 1813	ja	ja	ja	ja	ja	ja	ja			
Oil & Heat resistance	X	X	X	X	X	XXX	XX	X	X	X
Powerband	ja	ja	ja	ja		ja	ja		ja/ JB	
Voorbeeld bestelcode		C100/2	SPB3000/2	SPB3000/2		XPB3000/2	SPCP3000/2			PL2070-2
Powerband 2 snaren	X	X	X	X		X	X		X	X
Toerental hoog >									X	
Riemsnelheid max 30-35 m/s	X	X	X	X		X	X	X		
Riemsnelheid > 30 m/s dynamisch balanceren										
Aramide trekkoord							X	X		
Polyestertrekkoord	X	X	X	X	X	X			X	X
Hoog vermogen					X	X	X		X	
Weerstand slip							X	X		
Weerstand Schokbelasting							X	X		
Temperatuur (hogere temperatuur gedurende korte periodes)	(-30°C+60°C)	(-30°C+60°C)	(-30°C+60°C)	(-30°C+60°C)	(-30°C +60°C)	(-40°C +110°C)	(-30°C +60°C)		(-54°C +85°C)	(-30°C +60°C)